MONOCULAR NIGHT VISION GOGGLES

Features

- · Comfortable, flip-up headgear
- Multi-coated all-glass optics
- Wide angle infrared illuminator
- Head Mount Included
- Adjustable Interpupillary Distance
- Optional 3x, 5x and 8x lenses available
- Water and fog resistant
- Limited Two-Year Warranty

Lightweight, rugged and a top notch performer the CM-A207/307 is an exceptional choice for hands-free usage. This model features high resolution image intensifier, auto-brightness, and bright source shut-off. CM-A207/307 goggles also have a built-in IR for total darkness with indicator ON light within the FOV and flip. One CR123A, case and manual are included. CM-A207/307 is an excellent choice for hands-free night vision applications.

TECHNICAL SPECIFICATIONS

| Model | CM-A207 | CM-A307 |
|----------------------------|--------------------------------|-----------|
| Intensifier Level | Gen2+ | Gen3 |
| Magnification | 1x | |
| Lens System | F1:1.2, 25.8 mm | |
| Resolution, Ip/mm* | 40 - 45 | 64 |
| Field of View | 40° | |
| Range of Focus | 0.25 m to infinity | |
| Photocathode Type | S25 | GaAs |
| Proshield Lens Coating | Yes | |
| S/N(dB) | 12-21 | 21-24 |
| Optical Senstivity | 500-600 | 1500-1800 |
| Detection Distance | >220 | |
| Diopter Adjustment | +5/-5 | |
| Controls | Direct | |
| Eye Range Adjustment Range | 58-72mm | |
| Automatic Brightness | Yes | |
| Bright Light Cut-off | Yes | |
| Automatic Shut-off | Yes | |
| Infrared Illuminator | Yes | |
| IR Indicator | Yes | |
| Power Supply | 2.0-4.2V | |
| Battery type | 1 CR 123 lithium battery | |
| Continuous Working Hours | 80 (Infrared is not turned on) | |
| | 40 (Open Infrared) | |

| Figure Of Merit | <1250 | |
|--|-------------------|--|
| Mean Time Before Failure, Hours | 10,000 | |
| Operating Temperature | -40° to +50° C | |
| Storage Temperature | -50° to +70 °C | |
| Relative Humidity | 98% | |
| Environmental Rating | IP65 / IP67 | |
| Dimensions | 180 x 74 x 55.5mm | |
| Weight | 385 Grams | |
| Warranty | 2 years | |
| CERTIFICATIONS BY NABL LAB | | |
| Environment Protection (Low Temperature Test/High Temperature Test/Damp Heat | | |

Environment Protection (Low Temperature Test/High Temperature Test/Damp Heat Test/Vibration Test/Driving Rain Test/Operating Altitude Test) - JSS 55555:2000, (Ingression Protection(IP-67)) - IS/ IEC/EN 60529:2001, CE, FCC, ISO 9001:2015, ROHS.

*Design and specifications are subject to change without notice



